

REMARKS

This amendment is being filed along with a Request for Continued Examination (RCE) application in response to the final Office Action. Claims 1-2, 5-9, and 11-33 are canceled herein without prejudice. Claims 3-4 and 10 were previously canceled without prejudice. New claims 34-59 are added herein. No new matter has been added. With this amendment, claims 34-59 are pending in the application.

I. Objections

The Office Action objected to the specification “because it has URLs or browser executable code.” To address the objection a Substitute Specification (clean copy), along with a Redline Substitute Specification showing the changes in redline format, are being submitted herewith. The Substitute Specification contains no new matter.

In the Substitute Specification, the format of the various items such as “www.gslb.com” and “www.foo.com” have been amended/altered such that they are no longer browser-executable. Specifically, a “space” has been added after each punctuation mark (*e.g.*, after each period, dash, etc.) so that a browser would not read said items in the specification as executable code. Thus, the newly presented formats in the Substitute Specification are “www. gslb. com” and “www. foo. com”, for example. It is therefore respectfully submitted that the objections in the Office Action have now been properly addressed.

The Office Action also raised an objection due to a mis-numbering error in claims 31-33, and requested re-numbering of the claims. Specifically, two claims were mistakenly both numbered as claim “31.” In view of the cancellation of claims 1-33 and the presentation of new claims 34-59 herewith, it is respectfully submitted that this objection due to claim numbering is now rendered moot.

II. Information Disclosure Statement (IDS)

The Office Action indicated on pages 2-3 that the ten (10) non-published pending U.S. patent applications listed in the IDS filed on October 18, 2006 were not in compliance, and therefore were not considered. It is respectfully submitted that IDS filing requirements have

indeed been met, since copies of said 10 applications were indeed submitted with the October 18, 2006 IDS filing.

In a telephone conversation held with the Examiner on November 16, 2006, the Examiner explained that the copies of said 10 applications had not yet been electronically loaded into the USPTO system when the present Office Action was issued. Hence, the Office Action was issued with said 10 applications being indicated to be non-considered in the form PTO-1449. However, the Examiner indicated during the telephone conversation that said 10 applications now appear in the USPTO system (said 10 applications now appear on PAIR, for example) and confirmed that said copies were submitted along with the original October 18, 2006 IDS filing, and further indicated that he will indicate consideration thereof in the next communication. **Accordingly, it is kindly requested that the Examiner provide confirmation of entry and consideration of these 10 non-published pending U.S. patent applications in the next communication.**

Another IDS is being filed herewith, so as to submit new references for entry and consideration. Again, it is kindly requested that the Examiner also provide confirmation of entry and consideration of these new references in the next communication. Because this present IDS is being filed along with an RCE, no fee is required for this present IDS filing.

III. Discussion of new independent claim 34 and its dependent claims

The present Office Action appears to have rejected all of the previously presented claims under 35 U.S.C. § 102(b) as being anticipated by a white paper entitled "Server Load Balancing in Today's Web-Enabled Enterprise" (hereinafter "the White Paper"). In view of the cancellation of previously presented claims 1-2, 5-9, and 11-33, these rejections are rendered moot.

New claims 34-59 are being presented herein, and it is respectfully submitted that these claims are allowable over the White Paper. Further, the recitations in new claims 34-59 are supported by the original specification as filed. A discussion of the distinctiveness of new independent claim 34 and its dependent claims over the White Paper will be provided first.

New independent claim 34 recites, *inter alia*, “obtaining at said site switch mapping information indicative of a mapping between said private virtual IP address and a public virtual IP address” and “providing said mapping information from said site switch to at least one load balancing controller to enable said load balancing controller to update an address record to indicate said public virtual IP address as a virtual IP address configured at said site switch.” It is respectfully submitted that these limitations are not met by the White Paper.

For example, in originally rejecting former claim 14 that recited, *inter alia*, “sending the mapping information for the host servers ... from the first network device to the load balancing device,” pages 7-8 of the present Office Action cited page 6, item 4 of the White Paper as meeting this and other limitations by disclosing “Authoritative DNS provides a IP address information and send to Controller GSLB Switch” and “Controller GSLB Switch receives IP address information sent from Authoritative DNS” (emphasis ours). A similar interpretation of the White Paper was made in rejecting former claim 1 on page 5 of the present Office Action, where the authoritative DNS server was interpreted as sending the mapping information to the load balancing device.

However, new independent claim 34 specifies that the recited “configuring ... a private virtual IP address” and “obtaining ... mapping information” are “at said site switch,” and further specifies that the mapping information is provided “from said site switch to said load balancing controller.” Accordingly, since claim 34 specifically requires the mapping information to be provided from a site switch, the White Paper cannot meet this limitation since the authoritative DNS server (and not a site switch) has been interpreted by the Office Action as providing mapping information to a load balancing device. Thus, claim 34 is allowable over the White Paper.

Claim 34 further recites, *inter alia*, “enable said load balancing controller to update an address record to indicate said public virtual IP address as a virtual IP address configured at said site switch rather than treating said public virtual IP address as a real IP address.” It is respectfully submitted that none of these limitations are disclosed, taught, or suggested by the White Paper. For example, the White Paper is completely silent as to any

address record or updating thereof to indicate a public virtual IP address as a virtual IP address configured at a site switch.

Page 4 of the Office Action asserted that the terms “private VIP address” and “public VIP address” are simply associated with IP addresses of a network for limited access and “cannot be patentable features.” This assertion is respectfully traversed herein. The manner in which a private virtual IP address and a public virtual IP address are treated under claim 34 is indeed a distinction over the White Paper. That is in claim 34, if mapping information indicative of a mapping between a public virtual IP address and a private virtual IP address is provided to the load balancing controller, then the address record is updated, so that the public virtual IP address is not treated as a real IP address. Dependent claim 37 further elaborates by specifying that “public virtual IP addresses received by said load balancing controller that do not have corresponding indication in said address record as being configured as virtual IP addresses at any of said site switches, are treated as real IP addresses by said load balancing controller and are excluded from having applied thereto any metric of said load balancing algorithm that is usable with virtual IP addresses.” Accordingly, since the White Paper does not disclose, teach, or suggest the specific features recited in claims 34 and 37 directed towards a private virtual IP address and public virtual IP addresses, claims 34 and 37 are allowable.

Dependent claim 38 specifies that said at least one metric is “an active bindings metric that prefers a virtual IP address, associated with any of said site switches, having a maximum number of active ones of said host servers bound to said preferred virtual IP address, rather than preferring another virtual IP address having a number of bound active ones of said host servers that is less than said maximum number.” It is respectfully submitted that the limitations in claim 38 are not met by the White Paper.

For example, in originally rejecting former claim 29, page 10 of the present Office Action cited page 4 (first bullet under “Maximum Server Utilization”) of the White Paper as allegedly disclosing the “active bindings metric” recited in claim 29. This interpretation of the White Paper is respectfully traversed. The cited portion of the White Paper recites the following (emphasis ours):

“SLB is the general term assigned to techniques intended to provide: ... maximum server utilization ...”

Server Load Balancing or “SLB” is a network configuration wherein a plurality of servers (a “server farm”) sits behind a site switch. The servers of the server farm may be mapped to a virtual IP address configured on the site switch. The site switch receives traffic from clients that is addressed to the virtual IP address, and distributes/balances the traffic among its servers in the server farm. Thus, when the White Paper is speaking of “maximum server utilization” in the context of “SLB,” a person skilled in the art would interpret this description as describing a situation where the site switch attempts to balance traffic as best as possible by ensuring that all of its available servers of the server farm are used for load distribution and that not any one or more servers of the server farm are disparately burdened with traffic relative to other servers in the server farm.

Claim 38 pertains to a different situation than the SLB configuration and “server utilization” of the White Paper. Specifically, claim 38 states that the active bindings metric prefers a virtual IP address, associated with any of the site switches, having a maximum number of active host servers, rather than preferring another virtual IP address having a lesser number of active servers. Thus, claim 38 involves a situation where one virtual IP address is preferred over another virtual IP address based on the number of active host servers bound to them—this is different than the SLB configuration of the White Paper where there is only one (1) virtual IP address (*e.g.*, the virtual IP address configured on the site switch) and only one set of servers (in the server farm) bound to that single virtual IP address. In other words, the White Paper does not compare two or more virtual IP addresses with each other to determine which virtual IP address has a greater number of active host servers bound to it—instead, the cited portion of the White Paper is merely speaking of load distribution among servers bound to the same virtual IP address.

Thus, claim 38 is allowable over the White Paper.

IV. Discussion of other independent claims and their dependent claims

New independent claim 39 and its dependent claims are method claims having recitations that generally parallel some of the recitations of claim 34 and its dependent claims, except written from the perspective of the load balance switch. For reasons similar to those explained above with respect to claim 34 and its dependent claims, claim 39 and its dependent claims are also allowable over the White Paper.

Independent claims 43 and 47 (and their corresponding dependent claims) respectively include recitations generally parallel to those of claims 34 and 39 (and their corresponding dependent claims), and are allowable over the White Paper for similar reasons.

Independent claim 51 and its dependent claims are directed towards a site switch, while independent claim 56 and its dependent claims are directed towards a load balance switch. These claims include recitations that generally parallel those previously explained above with respect to the other independent claims, and are allowable over the White Paper for similar reasons.

V. Conclusion

Overall, none of the references of record singly or in any proper combination disclose, teach, or suggest what is recited in the independent claims. Thus, given the above amendments and accompanying remarks, the independent claims are now in condition for allowance. The dependent claims that depend directly or indirectly on these independent claims are likewise allowable based on at least the same reasons and based on the recitations contained in each dependent claim.

If the undersigned attorney has overlooked a teaching in any of the cited references that is relevant to the allowability of the claims, the Examiner is requested to specifically point out where such teaching may be found. Further, if there are any informalities or questions that can be addressed via telephone, the Examiner is encouraged to contact the undersigned attorney at (206) 622-4900.


Application No. 10/674,627
Reply to final Office Action dated November 3, 2006

The Director is authorized to charge any additional fees due by way of this Amendment, or credit any overpayment, to our Deposit Account No. 19-1090.

All of the claims remaining in the application are now clearly allowable.
Favorable consideration and a Notice of Allowance are earnestly solicited.

Respectfully submitted,

SEED Intellectual Property Law Group PLLC

A handwritten signature in black ink, appearing to read "Dennis M. de Guzman", written over a horizontal line.

Dennis M. de Guzman
Registration No. 41,702

DMD:wt

701 Fifth Avenue, Suite 5400
Seattle, Washington 98104-7092
Phone: (206) 622-4900
Fax: (206) 682-6031

949195

GLOBAL SERVER LOAD BALANCING SUPPORT FOR PRIVATE VIP ADDRESSES

BACKGROUND OF THE INVENTION

Field of the Invention

5 This disclosure relates generally to load balancing among servers. More particularly but not exclusively, the present disclosure relates to providing network components with capability to detect mapping between public and private addresses and to provide the public addresses for use in load balancing.

Description of the Related Art

10 Under the Transmission Control Protocol/Internet Protocol (TCP/IP), when a client provides a symbolic name (a Uniform Resource Locator or URL) to request access to an application program or another type of resource, the host name portion of the URL needs to be resolved into an IP address of a server for that application program or resource. For example, the URL (e.g.,
15 ~~http://www.foundrynet.com/index.htm~~ http://www.foundrynet.com/index.htm) includes a host name portion ~~www.foundrynet.com~~ www.foundrynet.com that needs to be resolved into an IP address. The host name portion is first provided by the client to a local name resolver, which then queries a local Domain Name System (DNS) server to obtain a corresponding IP address. If a corresponding IP
20 address is not locally cached at the time of the query, or if the time-to-live (TTL) of a corresponding IP address cached locally has expired, the DNS server then acts as a resolver and dispatches a recursive query to another DNS server. This process is repeated until an authoritative DNS server for the domain (e.g., *foundrynet.com*, in this example) is reached. The authoritative DNS server returns
25 one or more IP addresses, each corresponding to an address at which a server

hosting the application ("host server") under the host name can be reached.

These IP addresses are propagated back via the local DNS server to the original resolver. The application at the client then uses one of the IP addresses to establish a TCP connection with the corresponding host server. Each DNS server
5 caches the list of IP addresses received from the authoritative DNS server for responding to future queries regarding the same host name, until the TTL of the IP addresses expires.

To provide some load sharing among the host servers, global server load balancing (GSLB) switches are sometimes used as proxies for authoritative
10 DNS servers, together with one or more site switches each associated with one or more host servers. Each site switch provides the GSLB switch with current site-specific information ("metrics") regarding access conditions to the host servers associated with the site switches. The GSLB switch then processes the addresses returned by the DNS server using the metrics compiled from the site switches and
15 provides an ordered address list having the optimum address for access listed at the top. An example of a GSLB system and description of associated metrics are disclosed in U.S. Application Serial No. 10/376,903, entitled "GLOBAL SERVER LOAD BALANCING," filed February 28, 2003, assigned to the same assignee as the present application, and which is incorporated herein by reference in its
20 entirety.

An increasingly common feature of networks with internal and external connections is the mapping of private (internal) server addresses to public (external) addresses via a mapping device, such a firewall or Network Address Translation (NAT) device. Another frequent characteristic of such networks is the
25 use of virtual IP addresses (VIPs) in addition to real server addresses. A VIP can have either or both a private address and a public address. The authoritative DNS server for which a GSLB switch is being used as a proxy for the specified domains is typically configured with the public addresses for these domains, so that the GSLB switch can reorder these public addresses returned in the authoritative DNS

server reply as part of the GSLB algorithm when a client requests access to any of the specified domains. In addition to having a GSLB switch communicate directly with site switches to obtain metrics information from the site switches, the GSLB switch also receives from the site switches a list of VIPs configured on the site switches. If these VIPs are private IP addresses mapped to public IP addresses by a device such as a firewall or NAT device, then the site switch is unaware of the mapping and only communicates the private VIP addresses to the GSLB switch. However, since the authoritative DNS server is configured with the public addresses rather than with the private addresses, the public VIP addresses received in the DNS reply do not match the private VIP address on the GSLB switch and are treated as real addresses by the GSLB switch rather than as virtual addresses. Since most of the metrics are applicable only to virtual addresses and not to real addresses, the GSLB switch cannot apply many of the metrics to the received private address, thereby reducing the overall efficiency or accuracy of the load balancing system.

As a further elaboration, a VIP having a private IP address is configured on a site switch. The site switch would know the private IP address associated with that VIP, but would not know the public IP address mapped to that private IP address by a mapping device (such as a firewall device). As a result, the site switch would communicate only the private IP address (and its associated metrics information) rather than the public IP address to the peer GSLB switch. Meanwhile, the authoritative DNS server (for which the peer GSLB switch is serving as a proxy and for which the GSLB switch is handling load balancing for the site having the VIP) has been configured with only the public IP address for the VIP for that site. Accordingly, when the GSLB switch receives the DNS reply from the authoritative DNS server, the GSLB switch would not recognize the public IP address in the DNS reply as being a VIP at that site, since the GSLB switch is only aware of the private IP address of the VIP received from the site switch. The GSLB switch therefore treats the received public IP address as a real address,

since the private IP address is different from the public IP address in the DNS reply being reordered by the GSLB switch. Accordingly, the GSLB switch would not apply (or would incorrectly apply) some of the metrics, such as the active bindings metric (where the best IP address is the VIP that has the maximum number of
5 active real servers bound to it), which are usable only with virtual addresses. Had the GSLB switch been able to correctly identify the received address as being a VIP, the GSLB would have been able to apply the correct metric(s) for VIPs when reordering the reply from the authoritative DNS server for which it is serving as a proxy.

10 BRIEF SUMMARY OF THE INVENTION

One aspect of the present invention provides a method that includes obtaining information related to a mapping between first and second addresses associated with a network resource. The method sends the mapping information to a load balancing device to allow the load balancing device to load balance traffic
15 to the network resource using at least one metric associated with the second address and the mapping information.

The present invention is better understood upon consideration of the detailed description of the embodiments below, in conjunction with the accompanying drawings.

20 BRIEF DESCRIPTION OF THE DRAWINGS

Non-limiting and non-exhaustive embodiments of the present invention are described with reference to the following figures, wherein like reference numerals refer to like parts throughout the various views unless otherwise specified.

25 Figure 1 illustrates a GSLB system in which an embodiment of the invention may be implemented.

Figure 2 illustrates a GSLB system according to one embodiment of the invention with a remote load balancing arrangement.

Figure 3 illustrates a GSLB system according to another embodiment of the invention with a combination of remote and local load balancing
5 arrangement.

Figure 4 illustrates a GSLB system according to yet another embodiment of the invention with a combination of remote and local load balancing arrangement.

Figure 5 is a flowchart of a GSLB process to provide public
10 addresses according to an embodiment of the invention for a remote load balancing arrangement.

Figure 6 is a flowchart of a GSLB process to provide public addresses for only remote load balancing in an arrangement having both remote and local load balancing according to an embodiment of the invention.

Figure 7 is a flowchart of a GSLB process to provide public
15 addresses for both remote and local load balancing according to an embodiment of the invention.

DETAILED DESCRIPTION

Embodiments of techniques to provide GSLB support for private VIPs
20 are described herein. In the following description, numerous specific details are given to provide a thorough understanding of embodiments of the invention. One skilled in the relevant art will recognize, however, that the invention can be practiced without one or more of the specific details, or with other methods, components, materials, etc. In other instances, well-known structures, materials, or operations are not shown or
25 described in detail to avoid obscuring aspects of the invention.

Reference throughout this specification to "one embodiment" or "an embodiment" means that a particular feature, structure, or characteristic described in connection with the embodiment is included in at least one embodiment of the

present invention. Thus, the appearances of the phrases “in one embodiment” or “in an embodiment” in various places throughout this specification are not necessarily all referring to the same embodiment. Furthermore, the particular features, structures, or characteristics may be combined in any suitable manner in one or more embodiments.

As an overview, one embodiment of the present invention provides GSLB support for private VIPs. According to this embodiment, an authoritative DNS server, for which a GSLB switch is serving as a proxy, is configured with public IP addresses for a domain that the GSLB switch load balances. A site switch for the GSLB switch is configured with one or more private address of a VIP of the domain, with the site switch providing metrics information to the GSLB switch as part of the load balancing process. A mapping device maps the private addresses of the VIP to the public IP addresses.

The site switch obtains the mapping information from the mapping device, thereby being able to identify the public IP address of the VIP. The site switch then communicates all of the VIPs, configured on the site switch, to the GSLB switch. Because the site switch has identified the public IP address that is mapped to the private IP address configured on the site switch, the communication of the VIPs from site switch to the GSLB switch includes the public IP address instead of the private IP address. The GSLB switch receives the public IP address of the VIP from the site switch. The GSLB switch updates an address list/records it maintains for the site switch with the public IP addresses of the VIP. As a result, when the GSLB switch reorders the DNS reply from the authoritative DNS server, the GSLB switch references the address list and correctly identifies the IP address in the reply as a VIP on the site switch, since the IP address configured for the domain on the authoritative DNS server as well as that learned by the GSLB switch from the site switch now is the public IP address of the VIP. The GSLB switch is now able to apply the appropriate VIP-related metrics accurately to reorder the DNS reply to send to a requesting client.

According to various implementations, the site switch can be configured "for peer only" or "for self and peer." With the "for peer only" configuration, a GSLB controller on the site switch continues to use private IP addresses if the site switch also performs GSLB for the local site. With the "for self and peer" configuration, the site switch communicates the public IP addresses to a peer GSLB switch as well as to a local GSLB controller if the site switch is also functioning as a GSLB switch, thereby allowing the local GSLB controller of the site switch to accurately apply VIP-related metrics to load balance traffic.

Figure 1 shows one example of a global server load balancing arrangement in which an embodiment of the invention may be implemented. As shown in Figure 1, a remote (peer) GLSB switch 100 is connected to an Internet 104 and acts as proxy to an authoritative DNS server 102 for a network represented by the domain "*foo.com*" (for example). While the DNS server 102 provides the actual DNS service for the domain, the IP address known to the rest of the Internet 104 for the authoritative DNS server 102 is a VIP address configured on the GSLB switch 100. The DNS server 102 is also configured with the IP addresses for the domain *foo.com*, and the GSLB switch 100 is configured as a proxy for the domain *foo.com*. The GSLB switch 100 forwards client queries to the DNS server 102, and reorders the IP address list received from the authoritative DNS server 102 and sends the reordered IP address list in response to queries from clients requesting access to *foo.com*.

The network represented by the domain name *foo.com* has two components, for the purpose of describing an embodiment of this invention, in addition to other sub-parts. These components are a mapping device 106 and at least one site switch 108 (or other network device, such as a router). The mapping device 106 translates internal (private) addresses of real and virtual servers on the network to external (public) addresses. NAT or firewall devices are typical examples of such mapping devices 106.

The site switch 108 is coupled to an internal side of the mapping device 106. In addition to other tasks, the site switch 108 collects information about real and/or virtual servers 110 on the network and communicates with the GSLB switch 100. In particular, the site switch 108 has one or more VIPs

5 configured on it, and communicates to the GSLB switch 100 that it has these VIPs via a protocol exchange. This protocol exchange is also used to communicate VIP-related metrics information collected by the site switch 108 to the GSLB switch 100.

In a global server load balancing application, the GSLB switch 100,
10 acting as a proxy to the authoritative DNS server 102, receives a query from a client on the Internet 104 in the form of a URL that requests access to the domain *foo.com*, for example. The authoritative DNS server 102 provides a list of addresses to the GSLB switch 100 that corresponds to the domain *foo.com*. The GSLB switch 100 also gets metrics information along with a list of VIPs configured
15 on the site switch 108 from the site switch 108. Using the metrics information, the GSLB switch 100 reorders the list of addresses received from the authoritative DNS server 102 to place the optimum address at the top. For purposes of brevity, details of global server load balancing and performance metrics for load balancing will not be described in further detail herein, and instead are disclosed in U.S.
20 Application Serial No. 10/305,823, entitled "DISTRIBUTED HEALTH CHECK FOR GLOBAL SERVER LOAD BALANCING", filed November 27, 2002; U.S. Application Serial No. 10/376,903, entitled "GLOBAL SERVER LOAD BALANCING", filed February 28, 2003; and in U.S. Application Serial No. 10/211,822, entitled "STATISTICAL TRACKING FOR GLOBAL SERVER LOAD
25 BALANCING", filed August 1, 2002. All applications are assigned to the same assignee as the present application and incorporated herein by reference in their entirety.

In accordance with embodiments of the invention that will be described further below, the site switch 108 obtains mapping information between

public and private IP addresses on the network from the mapping device 106 and then communicates the VIPs configured on the site switch 108 to the GSLB switch 100, with the communication including the public IP address of the VIP rather than its private IP address. The GSLB switch 100 can then responsively update its address records 112 (e.g., a VIP list that the GSLB switch 100 maintains for the site switch 108) with the public IP address of the VIP. This public IP address of the VIP is also configured for the domain *foo.com* on the DNS server 102. The DNS server 102 returns a list of IP addresses, also containing the public IP address of the VIP, to the GSLB switch 100. The GSLB switch 100 refers to its address records 112 and correctly identifies the public IP address as a VIP on the site switch 108. Thus, the GSLB switch 100 can reorder the list of addresses received from the authoritative DNS server 102 based on the VIP-related metrics information and/or other metrics information provided by the site switch 108.

Examples of suitable topographies for load balancing with private VIP support include, but are not limited to, the following three arrangements in Figures 2-4. Figure 2 is a block diagram of a remote GSLB arrangement according to an embodiment of the invention. In this arrangement, a site switch 208 has no associated local GSLB sites and does not function as a GSLB switch itself (e.g., the site switch 208 has no local GSLB controller or metric collector). The site switch 208 operates as the remote site switch for a GSLB switch 200 (which load balances traffic to a network 224), and the GSLB switch 200 has no local site configured. Servers 210 have real IP addresses, and can have private VIP addresses configured on the site switch 208.

The network 224 can have a variety of mapping device arrangements. No mapping device, a mapping device integrated with the site switch 208, or an external mapping device connected to the site switch 208 are some of the examples. A mapping device 206 is shown in Figure 2, which may be a firewall, NAT, or other device that maps or otherwise allocates public IP addresses to the private IP addresses configured on the site switch 208. The

mapping information can be stored in one or more tables 220 or other data structure accessible by the site switch 208 in one embodiment.

There are several techniques that may be employed to allow the site switch 208 to obtain the mapping between the private and public IP addresses. In one embodiment, the mapping can be obtained via user configuration information. In this embodiment, a user can explicitly configure (such as via programming) the site switch 208 with the particulars of the mapping between the public IP addresses and the private IP addresses. In another embodiment, the mapping device 206 is integrated with the site switch 208, and the site switch 208 can directly obtain the mapping information from the table 220 (internal) or other entity that is maintained with the allocation of public IP addresses to private IP addresses. In yet another embodiment, the site switch 208 can obtain the mapping information through a message communication 226 with the mapping device 206, if the mapping device 206 is external to the site switch 208. The message communication 226 can be unidirectional or bi-directional movement of data between the site switch 208 and mapping device 206.

Then, the site switch 208 provides the obtained public IP addresses for the VIPs configured on it to the GSLB switch 200 that handles the remote load balancing for that particular network 224. According to one embodiment, the public IP addresses are provided to the GSLB switch 200 via a protocol message communication 222, along with related metrics information, instead of the private IP addresses. Alternatively or in addition in another embodiment, the information provided via the message communication 222 includes information indicative of the mapping between the public and private IP addresses, rather than solely the public IP addresses.

A specific example is now provided with regards to operation of the arrangement of Figure 2. Also provided to assist in explaining the operation is Figure 5, which is a flowchart of a GSLB process to provide public addresses according to an embodiment of the invention for the remote load balancing

arrangement of Figure 2. At least some components of the flowcharts depicted herein may be embodied in software or other machine-readable instructions stored on one or more machine-readable media. Such machine-readable media may be at a site switch, at a remote GSLB switch, or at other locations or combinations thereof. The various operations represented in the flowchart need not necessarily occur in the exact order depicted and some operations can be eliminated, added, or combined.

Initially in this example, the user configures a VIP 192.168.10.1 on the site switch 208. The VIP address 192.168.10.1 is a private IP address. The IP addresses (public) for a domain ~~www.gslb.com~~ www.gslb.com are 207.95.55.23 and 253.72.96.55, and which are configured on the DNS server 202. The GSLB switch 200 is serving as a proxy to the DNS server 202 and is providing GSLB for the domain ~~www.gslb.com~~ www.gslb.com.

The mapping device 206 maps the private IP address 192.168.10.1 of the VIP to one of the public IP addresses 207.95.55.23 (for example). The operations of Figure 5 begin with examples of different ways of providing mapping information to the site switch 208. Mapping information between the public and private IP addresses can be obtained by the site switch 208 via user configuration at a block 500, via access to internal allocation tables of an integrated mapping device at a block 502, via message communication with an external mapping device at a block 504, or via some other technique. Should the mapping information change at any time, the site switch 208 can re-learn the mapping. In addition to the mapping information (e.g., the public IP addresses), the site switch 208 also collects related metrics information at a block 506.

The site switch 208 is configured "for peer only" in this example, since the site switch 208 does not function as a GSLB controller/collector and does not have a local GSLB site configured. Therefore, the site switch 208 will be sending public IP addresses to the peer GSLB switch 200 only, to allow the peer GSLB switch 200 to perform load balancing accurately for the domain

~~www.gslb.com~~ www.gslb.com, rather than also sending public IP addresses to its internal GSLB components (which it does not have or are not enabled). The site switch 208, having obtained the mapping and metrics information, transmits that information to the GSLB switch 200 at a block 508. More specifically, the site switch 208 notifies the GSLB switch 200 that it has a VIP 207.95.55.23 configured on it. The GSLB switch 200 maintains a list (e.g., address records 212) of VIPs for each site switch, and at a block 510, updates the address 207.95.55.23 (to indicate that this address is a VIP) in the VIP list maintained for the site switch 208.

A client makes a query to the GSLB switch 200 requesting access to ~~www.gslb.com~~ www.gslb.com at a block 512, with the IP addresses configured on the authoritative DNS server 202 for the domain ~~www.gslb.com~~ www.gslb.com being 207.95.55.23 and 253.72.96.55. The GSLB switch 200 forwards the request to the DNS server 202 at a block 511, and the DNS server 202 sends an address list associated with the domain to the GSLB switch at a block 515 (i.e., the addresses 207.95.55.23 and 253.72.96.55 in this example). The GSLB site switch 200 refers to the address records 212 at a block 513 and can now correctly identify that 207.95.55.23 is a VIP on the site switch 208, since the GSLB switch 200 now has this IP address in the VIP list maintained for the site switch 208. The GSLB site switch 200 then performs GSLB on these IP address using the applicable metrics and selects the best IP address from among the addresses 207.95.55.23 and 253.72.96.55 at a block 514. Information reported by the site switch 208 can be used by the GSLB switch 200 for the VIP 207.95.55.23 during this selection process at the block 514, since the IP address 207.95.55.23 has been correctly identified as a VIP on the site switch 208. The final operation in the flowchart is the transmission of the ordered address list to the inquiring client at a block 516.

In the load balancing arrangement depicted in Figure 3, both remote and local load balancing are performed, except that the arrangement is configured "for peer only," where public IP addresses are communicated only to a remote peer GSLB switch 300 from a site switch 308, which performs its own ("self") local

GSLB but does not communicate public IP addresses to its own internal GSLB components.

To further elaborate, the site switch 308 performs GSLB for one or more associated local sites 312 and remote sites (if any), and in addition is the site switch for the GSLB switch 300 that load balances traffic to a site 314 having host servers 310 coupled to the site switch 308. The site switch 308 is configured with the private VIP addresses to which the servers 310 of the site 314 are bound and obtains at 324 mapping information from a mapping device 306, which maps these private VIP addresses to public IP addresses. The public IP addresses are obtained from the mapping device 306 using techniques previously described above, and as before with reference to Figures 2 and 5, the public IP addresses are communicated (along with related metrics information) by the site switch 308 to the GSLB switch 300 via a protocol message communication 316, so that the GSLB switch 300 can update its VIP list with the public IP address of the VIP.

The site switch 308 is also configured with the private IP addresses associated with the local site 312. However, since the site switch 308 is configured "for peer only," the site switch 308 does not send any public IP addresses associated with the local site 312 to the internal GSLB components 318 (e.g., a local GSLB controller or metric collector) integrated within the site switch 308. Rather, the site switch 308 sends the private VIP addresses configured on it to the internal GSLB components 318.

An example description of the operation of the arrangement of Figure 3 will now be provided in conjunction with a flowchart of Figure 6. The GSLB switch 300 provides GSLB for a domain ~~www.gslb1.com~~ www.gslb1.com. The public IP addresses configured for ~~www.gslb1.com~~ www.gslb1.com on an authoritative DNS server 302 are 207.95.55.23 and 253.72.96.55. As explained above, the GSLB switch 300 does not have any local site configured, and has one remote site 314 with the site switch 308 (e.g., the site switch 308 is a site switch for the GSLB switch 300).

In addition to being a site switch for the GSLB switch 300, the site switch 308 itself is also a GSLB switch that provides GSLB for a domain ~~www.foo.com~~ www.foo.com at the local site 312. The IP addresses configured for the domain ~~www.foo.com~~ www.foo.com on an authoritative DNS server 322 are 192.168.10.1 and 192.168.72.1, which are private IP addresses. Accordingly, the site switch 308 provides GSLB for the domain ~~www.foo.com~~ www.foo.com and is the local site switch used by its internal GSLB components 318. In addition, the site switch 308 operates as the remote site switch for the GSLB switch 300, which provides GSLB for the domain ~~www.gslb1.com~~ www.gslb1.com.

10 When the “for peer only” configuration is completed on the site switch 308, the site switch 308 will do the following:

1) Since the site switch 308 is a remote site switch for the GSLB switch 300, the site switch 308 will communicate the VIPs configured on it via the message communication 316 to the GSLB switch 300. In particular, the site switch 15 308 obtains the mapping information including the public IP addresses for the site 314 from the mapping device 306 at a block 600, and will notify the GSLB switch 300 that the site switch 308 has a VIP 207.95.55.23 configured on it at a block 602. The GSLB switch 300 maintains address records 320 of VIPs for each site switch and at a block 604, updates the VIP address as 207.95.55.23 in the VIP 20 records maintained for the site switch 308.

2) In addition, the site switch 308 is also a local site for the site switch 308 operating as a GSLB switch. Therefore, the site switch 308 will communicate the VIPs configured on it to its internal GSLB components 318 (along with metrics information) at a block 606. However, since the user has configured the “for peer 25 only” option for one of the private VIP addresses (say 192.168.10.1, for instance), the local site switch 308 will notify its internal GSLB components 318 that it has a private VIP 192.168.10.1 configured on it--note that it does not communicate the public IP address of the VIP to the internal GSLB components 318.

A client makes a query for ~~www.foo.com~~ www.foo.com, which the site switch 308 receives as a request to access the site 312 at a block 608, and forwards the request to the DNS server 322 at a block 609. The IP addresses configured for the domain ~~www.foo.com~~ www.foo.com on the DNS server 322 are
5 192.168.10.1 and 192.168.72.1. The DNS server 322 sends the list of addresses containing 192.168.10.1 and 192.168.72.1 to the internal GSLB components 318. The internal GSLB components 318 refer to its address records 326 at a block 619 and correctly identify that 192.168.10.1 is a VIP configured on the local site switch 308, since the internal GSLB components 318 has this IP address in the VIP list it
10 maintained for the site switch 312. The internal GSLB components 318 then perform GSLB on these IP addresses using the appropriate metrics and selects the best IP address for the client at a block 610. Metric information reported by the site switch 308 can be used by the internal GSLB components 318 for the VIP 192.168.10.1 during the selection process at the block 610. The prioritized list of
15 addresses is sent to the requesting client at a block 612.

If a client makes a query for ~~www.gslb1.com~~ www.gslb1.com to the GSLB switch 300 to request access to the site 314 at a block 614, the IP addresses configured for the domain ~~www.gslb.com~~ www.gslb.com on the DNS server 302 are 207.95.55.23 and 253.72.96.55. The GSLB switch 300 sends this
20 request to the DNS server 302 at a block 615, and receives a list of addresses containing the addresses 207.95.55.23 and 253.72.96.55 from the DNS server 302 at a block 617. The GSLB switch 300 refers to its address records 320 at the block 619, and correctly identifies that 207.95.55.23 is a VIP on the site switch 308, since the GSLB switch 300 has this IP address in the VIP list maintained for
25 the site switch 308. The GSLB switch 300 then performs GSLB on these IP addresses using the appropriate metrics and selects the best IP address for the client at the block 610. Information reported by the site switch 308 can be used by the GSLB switch 300 for the VIP 207.95.55.23 during the selection process at the

block 610, since the IP address 207.95.55.23 has been correctly identified as a VIP on the site switch 308.

Under another remote and local combination load balancing aspect of an embodiment of the invention shown in Figure 4, the site switch 308 can be configured "for self and peer," wherein public IP address are provided by the site switch 308 to both the peer GSLB switch 300 and the internal GSLB components 318 integrated within the site switch 308. As with the embodiment of Figure 3, the remote GSLB switch 300 receives metric information regarding servers 310 from the local site switch 308 and performs the load balancing for the site 314. The local site switch 308 also acts as an independent GSLB switch for the local site 312 and handles its load balancing based on the public IP addresses and metrics information received by its internal GSLB components 318 from other internal components 400 of the site switch 308. A requesting client would query the remote GSLB switch 300 for addresses of domains it is providing GSLB for. Similarly, the requesting client would query the GSLB controller at the site switch 308 for addresses for domains the site switch 308 is providing GSLB for.

Another example is now provided to illustrate operation of the arrangement of Figure 4 in connection with the "for self and peer" configuration, which is also to be described in connection with the flowchart of Figure 7. The GSLB switch 300 provides GSLB for the domain ~~www.gslb1.com~~ www. gslb1. com. The public IP addresses configured for ~~www.gslb1.com~~ www. glsb1. com on the DNS server 302 are 207.95.55.23 and 253.72.96.55. The GSLB switch 300 does not have any local site configured, and uses the site switch 308 as its remote site switch.

Additionally, the site switch 308 is also a GSLB switch providing GSLB for the domain ~~www.foo.com~~ www. foo. com, with the site switch 308 itself functioning as the site switch for its internal GSLB components 318. The public IP addresses configured for the domain ~~www.foo.com~~ www. foo. com on the DNS

server 322 are 207.95.55.23 and 245.20.72.1, with the private IP address 192.168.10.1 being mapped to the public IP address 207.95.55.23.

When the “for self and peer” configuration is performed on the site switch 308, the site switch 308 will perform the following:

- 5 1) Since the site switch 308 is a remote site switch for the GSLB switch 300, the site switch 308 will communicate the VIPs configured on the site switch 308 via the message communication 316 to the GSLB switch 300. In particular, the site switch 308 obtains (at 324 in Figure 4) the mapping information including the public IP addresses for the site 314 from the mapping device 306 at a
10 block 700, and will notify the GSLB switch 300 that the site switch 308 has a VIP 207.95.55.23 configured on it at a block 702. The site switch 308 also sends metrics information to the GSLB switch 300. The GSLB switch 300 maintains address records 320 of VIPs for each site switch, and at a block 704, updates the VIP address as 207.95.55.23 in the VIP records maintained for the site switch 308.
- 15 2) In addition, site switch 308 is also a local site for the internal GSLB components 318. Therefore, components 400 will obtain mapping information between private and public IP addresses associated with the site 312 at a block 706 and will communicate the VIPs configured on the site switch 308 to the internal GSLB components 318 at a block 708. Since user has configured the “for
20 self and peer” option for the VIP 192.168.10.1, the internal components 400 will notify the internal GSLB components 318 that the VIP 207.95.55.23 is configured on the site switch 308 at the block 708--note that the public IP address of the VIP is communicated to the internal GSLB components 318. If necessary, address records 326 are updated by the internal GSLB components 318 to indicate that the
25 public IP address 207.95.55.23 corresponds to a VIP on the site switch 308.

The IP addresses configured for the domain ~~www.foo.com~~ www.foo.com on the DNS server 322 are 207.95.55.23 and 245.20.72.1. If a client makes a query to the site switch 308 at a block 712 for the domain ~~www.foo.com~~ www.foo.com, the site switch 308 forwards the request to the DNS

server 322 at a block 713, and receives a list of addresses containing 207.95.55.23 and 245.20.72.1. The internal GSLB components 318 refers to the address records 326 at a block 719, and correctly identify that 207.95.55.23 is a VIP on the local site switch 308, since this public IP address is now kept in the VIP list (e.g., the address records 326) maintained for the site switch 308. The internal GSLB components 318 then perform GSLB on these IP addresses using the appropriate metrics and selects the best IP address for the client at a block 714. Metric information reported by the site switch 308, or more particularly by the components 400, can be used by the internal GSLB components 318 for the VIP 207.95.55.23 during the selection process at the block 714.

The IP addresses configured for the domain ~~www.gslb1.com~~ www.gslb1.com on the DNS server 302 are 207.95.55.23 and 253.72.96.55. If a client makes a query to the GSLB switch 300 for the domain ~~www.gslb1.com~~ www.gslb1.com at a block 716, the GSLB switch 300 forwards the request to the DNS server 302 at a block 717, and receives a list of addresses containing 207.95.55.23 and 253.72.96.55. The GSLB switch 300 refers to the address records 320 at the block 719, and correctly identifies that 207.95.55.23 is a VIP on the site switch 318, since this IP address in the VIP list (e.g., the address records 320) maintained for the site switch 308. The GSLB switch 300 then performs GSLB on these IP addresses using the appropriate metrics and selects the best IP address for the client at the block 714. Information reported by the site switch 308 can be used by the GSLB switch 300 for the VIP 207.95.55.23 during the selection process at the block 714, since the IP address 207.95.55.23 has been correctly identified as a VIP on the site switch 308. The prioritized list of addresses is sent to the requesting client at a block 718.

All of the above U.S. patents, U.S. patent application publications, U.S. patent applications, foreign patents, foreign patent applications and non-patent publications referred to in this specification and/or listed in the Application Data Sheet, are incorporated herein by reference, in their entirety.

The above description of illustrated embodiments of the invention, including what is described in the Abstract, is not intended to be exhaustive or to limit the invention to the precise forms disclosed. While specific embodiments of, and examples for, the invention are described herein for illustrative purposes, various
5 equivalent modifications are possible within the scope of the invention and can be made without deviating from the spirit and scope of the invention.

These and other modifications can be made to the invention in light of the above detailed description. The terms used in the following claims should not be construed to limit the invention to the specific embodiments disclosed in the
10 specification and the claims. Rather, the scope of the invention is to be determined entirely by the following claims, which are to be construed in accordance with established doctrines of claim interpretation.

15